

Volume Payload:

The Flexitank must be loaded with approved liquid cargo, and the difference between capacity and volume should be less than +/-500 litres. Flexitanks must be filled to correct volume capacity as confirmed by PBS International Fze.

Product Loading Temperatures Allowance:

Liquid cargoes must be loaded at temperature controlled between 75°C and -20°C, the latter applies to temperatures in the country of origin and destination also.

Liquid Products Acceptance:

General Liquid Products of Food and Non-Hazardous Chemical Grade

MSDS and other information of the liquid is to be provided to and confirmed by

PBS International Fze as being suitable for carriage in PBS Flexitanks.

<u>Recommended Use:</u>Single use flexitank for foodstuff, pharmaceutical, non – hazardous chemical or Industrial products.

Products Application

i cacioni	
Industrial Grease	Non-hazardous liquid chemicals
Lubricants	Plasticizer
Lubricants Additives	Synthetic Resins
White Oils	Cleanser
Tung oil	Disinfectant
Base Oil	Surfactant
Transformer Oils	Polyalcohol
Refined Oil	Feed Additives
Process Special Oil	Silicates
Vegetal Oil	Salt Solutions
Glycerin	Printing Oil
Coconut Oil	Propanediol
Hydraulic Oil	Glycol
Industrial Gear Oil	Polyether
Mineral Oils	Alkylation agent
Ricinus Oil	Herbicide
Biodiesel	Natural Latex
	Synthetic Latex
Other Non-hazardous liquid	Other Non-hazardous liquid
	Industrial Grease Lubricants Lubricants Additives White Oils Tung oil Base Oil Transformer Oils Refined Oil Process Special Oil Vegetal Oil Glycerin Coconut Oil Hydraulic Oil Industrial Gear Oil Mineral Oils Ricinus Oil Biodiesel